



Southwire™

90° BELL END ELBOWS

SCHEDULE 40 PVC

FEATURES

- A section of Schedule 40 PVC conduit which has been heated and bent to enable a 90° directional change in a conduit run
- A standard conduit bell is formed on one end while the other end is a spigot (plain) end
- Both ends are solvent weld

APPLICATION

- Can be used above ground or buried; suitable for use in concrete encasement


STANDARD MATERIAL

- Schedule 40 PVC



1241TZ

PART #	SIZE	MASTER QTY.	WEIGHT/ CASE (LBS.)	A MIN. RADIUS
1241TZ	1/2"	50	7	4
1242	3/4"	35	8	4.50
1243	1"	20	8	5.75
1244	1-1/4"	30	20	7.25
1245TZ	1-1/2"	30	25	8.25
1246TZ	2"	15	27	9.50
1247	2-1/2"	18	41	10.50
1248	3"	14	56	13
1249	3-1/2"	12	64	15
1250	4"	10	70	16
1250A	5"	1	8	24
1250B	6"	1	9	30



Rev. 0, 03/23

**BUILT FOR DURABILITY.
BUILT FOR RELIABILITY.
BUILT FOR WORK.™**

1-855-798-6657 | SOUTHWIRE.COM

©2023 Southwire Company, LLC. All rights reserved.
*Registered Trademark & ™Trademark of Southwire Company, LLC.