



Southwire™

EMT ELBOWS

45° - GALVANIZED STEEL

FEATURES

- Low conductivity, high corrosion resistance
- Smooth defect free interior and exterior

APPLICATIONS

- For a secure connection to EMT conduit; bend enables directional changes in conduit

STANDARD MATERIAL

- Galvanized steel

CERTIFICATIONS


- UL Standard: UL 797
- Fed. Spec: WW-C-563
- NEMA: ANSI C80.3-2015



21



PART #	SIZE	INNER QTY.	MASTER QTY.	WEIGHT/ CASE (LBS.)	(A) MIN. UL RADIUS	(B) STRAIGHT LEG EACH END
21	1/2"	---	50	11	4"	2.875"
22	3/4"	---	50	19	4.50"	2.875"
23	1"	---	35	25	5.75"	3"
24	1-1/4"	---	30	30	7.25"	3.25"
25TZ	1-1/2"	---	15	44	8.25"	3.625"
26TZ	2"	---	15	31	9.50"	4.1875"
27TZ	2-1/2"	1	50	250	10.50"	5.25"
28	3"	1	40	280	13"	5.8125"
29TZ	3-1/2"	1	35	315	15"	6.75"
30	4"	1	35	420	16"	6.9375"



Rev. 0, 03/23

**BUILT FOR DURABILITY.
BUILT FOR RELIABILITY.
BUILT FOR WORK.™**

1-855-798-6657 | SOUTHWIRE.COM

©2023 Southwire Company, LLC. All rights reserved.
*Registered Trademark & ™Trademark of Southwire Company, LLC.