



Southwire™

COMPRESSION LUG SPLICES

LONG BARREL

FEATURES

- Seamless, high conductivity copper tubing, suitable for heavy duty applications
- Tin-plated to provide corrosion resistance
- Color coded

APPLICATIONS

- Suitable for use at voltages up to 35 KV provided connector is properly taped
- 5 KV is the maximum voltage in all bare splice applications

STANDARD MATERIAL

- Copper

STANDARD FINISH


- Tin plated



3101TZ



PART #	WIRE SIZE	COLOR CODE	INNER QTY.	MASTER QTY.	WEIGHT/ CASE (LBS.)	A	B
3101TZ	#8	RED	100	1000	22	1.75"	.20"
3102	#6	BLUE	100	1000	22	1.75"	.20"
3103	#4	GRAY	100	1000	26	1.75"	.25"
3105TZ	#2	BROWN	50	500	21	1.90"	.31"
3106	1/0	PINK	25	250	19	2.20"	.39"
3107	2/0	BLACK	25	250	20	2.25"	.44"
3108	3/0	ORANGE	25	250	23	2.25"	.49"
3109	4/0	PURPLE	25	250	32	2.75"	.55"
3109A	250 MCM	YELLOW	10	100	20	3.25"	.59"
3109B	300 MCM	WHITE	10	100	23	3.50"	.66"
3110TZ	350 MCM	RED	10	100	28	3.75"	.70"
3110A	400 MCM	BLUE	10	100	32	3.75"	.76"
3111TZ	500 MCM	BROWN	5	50	25	4.25"	.83"
3111A	600 MCM	GREEN	5	50	34	4.50"	.93"
3112	750 MCM	BLACK	5	50	41	4.75"	1.03"



Rev. 0, 10/23

**BUILT FOR DURABILITY.
BUILT FOR RELIABILITY.
BUILT FOR WORK.™**

1-855-798-6657 | SOUTHWIRE.COM

©2023 Southwire Company, LLC. All rights reserved.
*Registered Trademark & ™Trademark of Southwire Company, LLC.