



Southwire™

ALUMINUM HOOK SHEAVES

- Oil-impregnated bushings deliver self-lubrication for smooth operation and long service life
- Axle support doublers improve load-bearing capacity with 2X axle arm thickness
- Axle anti-rotation stops prevent axle rotation during sheave operation, ensuring efficient bearing performance and reduced wear
- Welded box-style frame provides superior strength and stiffness
- Heat-treated cast aluminum alloy sheaves provide high strength, low weight, and corrosion resistance
- Forged steel swivel hooks allow smooth load alignment and reduce twisting

**HEAT-TREATED CAST
ALUMINUM ALLOY SHEAVE**

AXLE SUPPORT DOUBLERS

OIL-IMPREGNATED BUSHINGS

AXLE ANTI-ROTATION STOP

WELDED BOX-STYLE FRAME

FORGED STEEL SWIVEL HOOKS

SPRING-LOADED SAFETY LATCH



SHS24-4
66112940



SHS24
65122201



SHS18
65122101



SHS12
65122001



SHS6
65121901

MODEL #	MATERIAL #	DESCRIPTION	SHEAVE DIAMETER (IN)	SHEAVE WIDTH (IN)	HEIGHT (IN)	WIDTH (IN)	DEPTH (IN)	WEIGHT (LB)	HOOK OPENING SIZE (IN)	WORKING LOAD (LB)
SHS6	65121901	HOOK SHEAVE, 6" AL	6	5	17	7	6	13	1.1	6,000
SHS12	65122001	HOOK SHEAVE, 12" AL	12	5	23	7	12	22	1.1	6,000
SHS18	65122101	HOOK SHEAVE, 18" AL	18	6	29	8	18	35	1.1	6,000
SHS24	65122201	HOOK SHEAVE, 24" AL	24	7	36	9	24	54	1.4	10,000
SHS24-4	66112940	HOOK SHEAVE 24", TWIN YOKE AL	24	7	48	10	24	72	1.4	10,000

Rev.1, 05/26

**BUILT FOR DURABILITY.
BUILT FOR RELIABILITY.
BUILT FOR WORK.™**

1-855-798-6657 | SOUTHWIRE.COM

©2026 Southwire Company, LLC. All rights reserved.
*Registered Trademark & ™Trademark of Southwire Company, LLC.